## **AMENDMENT**

In the Claims:

Please amend claims 1, 12, 15 and 19 as follows:

1. (Currently Amended) A method of lowering the amount of carbon in fly ash resulting from the combustion of coal, the method comprising

combining coal and an additive that comprises an organometallic manganese compound in a coal burning combustion chamber forming a mixture therein, wherein the manganese compound is mononuclear or comprises small clusters of manganese atoms; and

combusting said mixture in said combustion chamber,

the manganese compound being present in an amount effective to lower the amount of carbon in fly ash resulting from the combusting of the coal in the combustion chamber.

- 2. (Canceled) The method as described in claim 1, wherein the manganese compound is an organometallic compound.
- 3. (Previously Amended) The method as described in claim 1, wherein the organometallic compound is selected from the group consisting of alcohols, aldehydes, ketones, esters, anhydrides, sulfonates, phosphonates, chelates, phenates, crown ethers, carboxylic acids, amides, acetyl acetonates and mixtures thereof.
- 4. (Previously Amended) The method described in claim 1, wherein the organometallic compound comprises methylcyclopentadienyl manganese tricarbonyl.

Amendment & Response Application No: 10/623,092 Attorney Docket No.: EI-7592

- 5. (Previously Amended) The method described in claim 1, wherein the organometallic manganese compound is selected from the group consisting of: cyclopentadienyl manganese tricarbonyl, methylcyclopentadienyl manganese tricarbonyl, dimethylcyclopentadienyl manganese tricarbonyl, trimethylcyclopentadienyl manganese tricarbonyl, tetramethylcyclopentadienyl manganese tricarbonyl, pentamethylcyclopentadienyl manganese tricarbonyl, diethylcyclopentadienyl manganese tricarbonyl, propylcyclopentadienyl manganese tricarbonyl, isopropylcyclopentadienyl manganese tricarbonyl, tert-butylcyclopentadienyl manganese tricarbonyl, octylcyclopentadienyl manganese tricarbonyl, dodecylcyclopentadienyl manganese tricarbonyl, ethylmethylcyclopentadienyl manganese tricarbonyl, indenyl manganese tricarbonyl, including mixtures of two or more of these compounds.
- 6. (Canceled) The method of claim 1, wherein the manganese-containing compound is selected from the group consisting of manganese oxides, manganese sulfates, and manganese phosphates.
- 7. (Original) The method as described in claim 1, wherein the manganese compound comprises about 20 ppm wt% of the coal.
- 8. (Original) The method as described in claim 1, wherein the manganese compound comprises about 5 to 100 ppm wt% of the coal.
- 9. (Original) The method as described in claim 1, wherein the manganese compound comprises about 2 to 500 ppm wt% of the coal.

Amendment & Response Application No: 10/623,092

Attorney Docket No.: EI-7592

10. (Original) A method as described in claim 1, wherein the additive is introduced into

an air stream that carries the coal into the combustion chamber.

11. (Original) The method as described in claim 1, wherein the manganese compound

comprises a mononuclear compound.

12. (Currently Amended) A method of reducing both the amount of carbon in fly ash

resulting from the combustion of coal, the method comprising

combusting coal and an additive that comprises an organometallic manganese-containing

compound in a combustion chamber, wherein the manganese compound is mononuclear or

comprises small clusters of manganese atoms;

the manganese-containing compound being present in an amount effective to reduce the

amount of carbon in fly ash resulting from the combusting of the coal in the combustion

chamber, wherein the additive is introduced directly into the combustion chamber separately

from the coal.

13. (Original) The method as described in claim 12, wherein the additive is introduced

into a flue gas recirculation stream.

14. (Original) The method as described in claim 12, wherein the additive is introduced

into a secondary air stream that is delivered into the combustion chamber.

4

15. (Currently Amended) A method of reducing the amount of carbon in fly ash resulting from the combustion of coal, the method comprising:

combining coal and an additive that comprises an organometallic manganese compound to form a mixture thereof, wherein the manganese compound is mononuclear or comprises small clusters of manganese atoms;

introducing the mixture of coal and additive into a coal burning combustion chamber; combusting the mixture in the combustion chamber;

the manganese compound being present in an amount effective to reduce the amount of carbon in fly ash resulting from the combustion of the coal in the combustion chamber.

- 16. (Original) A coal additive for use in reducing the amount of carbon in the fly ash resulting from the combustion of coal, the additive comprising a manganese compound wherein the manganese compound is added to the coal prior to the combustion at a treat rate of about 1 to 500 ppm of the coal.
- 17. (Original) The coal additive as described in claim 16, wherein the manganese compound is added to the coal prior to combustion at a treat rate of about 5 to 100 ppm of the coal.
- 18. (Original) The coal additive as described in claim 16, wherein the manganese compound is added to the coal prior to combustion at a treat rate of about 20 ppm of the coal.
  - 19. (Currently Amended) A method of reducing the amount of carbon in fly ash resulting

Amendment & Response Application No: 10/623,092

Attorney Docket No.: EI-7592

from the combustion of coal, the method comprising combining coal and an additive that

comprises a manganese-containing compound forming a mixture thereof; and combusting said

mixture in a combustion chamber; the manganese-containing compound being present in an

amount effective to reduce the amount of carbon in fly ash resulting from the combusting of the

coal in the combustion chamber wherein the manganese\_compound is an organometallic

compound, wherein the manganese compound is mononuclear or comprises small clusters of

manganese atoms.

20. (Original) A method of reducing the amount of carbon in fly ash resulting from the

combustion of coal, the method comprising combusting coal in the presence of at least 1 ppm of

a manganese-containing additive, whereby the amount of carbon in fly ash resulting from the

combustion of said coal is reduced relative to the amounts of carbon in fly ash resulting from the

combustion of coal in the absence of the manganese-containing additive.

21. (Previously Presented) The additive as described in claim 16, wherein the manganese

compound is an organometallic compound.

6